



## EASY 625

**5 Axis Mono-Block Bridge Saw.** Machine with compact dimensions. The spin of the head 360°. All the Axis drivers complete with elevated inertia BRUSHLESS motors. Complete CNC control with a Touch screen panel.

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Bridge Saws](#), [Terzago Macchine](#)

### Product Description

- Slide of disc-holder slips on guides in hardened steel, cold-drawn, in a class of precision H and sliding-block with recirculating balls pre-loaded for the elimination of the mechanical clearance.
- Positioning with pinion- helical rack system of precision and epicycle reducer with 0 clearance (Axis X).
- Sliding of the bridge on guides in hardened steel, cold-drawn, in a class of precision H and sliding-block with recirculating balls pre-loaded.
- Positioning with 2 motors in electrical-axis with pinion- helical rack system of precision and epicycle reducers with 0 clearance (Axis Y).
- Sliding of head-holder on the over-dimensioned chromed cylinder.
- Positioning with system screw-nut with recirculating balls pre-loaded and epicycle reducer with 0 clearance (Axis Z).
- Spin of the head  $\pm 185^\circ$  with a reducer of high precision with eccentrics with 0 clearance (Axis C).
- Spin of the mandrel  $0^\circ-90^\circ$  reducer of high precision with eccentrics with 0 clearance (Axis A).
- All the drives complete with elevated inertia BRUSHLESS motors, digitally controlled with system CAN-BUS.
- Disc motor, power 11 kW, directly connected to the blade, electronic control of rotation speed by mean of INVERTER.
- Possibility of tilted cut in small steps obtained with interpolation of the axis horizontal and vertical.
- Switchboard with isolation IP 55 at the right of the machine and outside of the foundation wall, with the general switch and block door. In the control panel are grouped the contactors with the relative thermal protections, the drives, and the electronic controls, the complete CNC control while the Touch screen panel and the keyboard are positioned in a remote pendant box.
- Laser beam facilitates positioning of the blade on the cutting line.
- Water pressure switches stop the machine if cooling water insufficient.
- Tools are protected by an electronic ammeter to prevent the use of above-preset values.
- Refrigeration pipes and electrical wiring protected in plastic cable trailer chain